



TOTAL

PRODUCT SPECIFICATIONS

FINAVESTAN A 360 B White Mineral Oil

CHARACTERISTICS	METHODS	UNITS	SPECIFICATIONS		Certificate of Analysis
			Min.	Max.	
Appearance	Visual	-	Clear & Bright		Yes
Odor	Olfactory	-	Absent		Yes
Color, Saybolt	ASTM D 156	-	+ 30	-	Yes
Kinematic Viscosity @ 40°C	ISO 3104, ASTM D 445	mm ² /s	65.0	75.0	Yes
Kinematic Viscosity @ 100°C	ISO 3104, ASTM D 445	mm ² /s	8.5	-	No
Density @ 15°C	ISO 12185, ASTM D 4052	kg/m ³	858.8	874.0	No
Density @ 20°C	ISO 12185, ASTM D 4052	kg/m ³	855.0	871.0	Yes
Pour Point	ASTM D 97	°C	-	- 12	Yes
Flash Point	ASTM D 92	°C	240	-	Yes
Polycyclic Aromatic Hydrocarbons (PAH)	European Pharmacopoeia (most recent edition)	-	Pass		Yes
Readily Carbonisable Substances	European Pharmacopoeia (most recent edition)	-	Pass		Yes
Solid Paraffins	European Pharmacopoeia (most recent edition)	-	Pass		No
Refractive Index, nD20 *	ASTM D 1218	-	1.476 *		No

* Typical value

Nanterre, 12th September 2012
Elisa MAURO, Product Manager

Adresse postale : 562 avenue du Parc de l'Île - 92029 Nanterre Cedex
Tél. +33 (0) 1 41 35 40 00

TOTAL LUBRIFIANTS

Société Anonyme au capital de 27 085 708 euros
Siège social : 562 avenue du Parc de l'Île - 92029 Nanterre
552 006 454 RCS Nanterre

